

AMENDMENTS TO THE CLAIMS

1. (currently amended) A golf putter having a shaft with a grip at a proximal end and a head at a distal end of the shaft for contacting a golf ball on the ground during putting of the golf ball,
5 the improvement in the head which comprises:

an elongate flat blade having opposed ends, with a top side and a bottom side, and a first linear edge extending therebetween, wherein the top side of the blade is mounted on the distal end of the shaft and the first linear edge acts as a striking face for the golf ball and strikes the golf ball in an essentially linear contact area horizontal to the ground, and wherein a single
10 groove extends along a length of the striking face.

2. (canceled)

3. (original) The putter of Claim 1 wherein the striking face is sharp, pointed, flat, or
15 curved.

4. (original) The putter of Claim 1 wherein a single groove extends along a length of the striking face.

20 5. (original) The putter of Claim 1 wherein the striking face is curved with a radius of curvature less than a radius of the golf ball.

6. (canceled)

7. (currently amended) A golf putter having a shaft with a grip at a proximal end and a head at a distal end of the shaft for contacting a golf ball on the ground during putting of the golf ball, the improvement in the head which comprises:

(a) an elongate flat blade having opposed ends, with a top side and a bottom side, and a first linear edge extending therebetween, wherein the top side of the blade is mounted on the distal end of the shaft and the first linear edge acts as a striking face for the golf ball and strikes the golf ball in an essentially linear contact area horizontal to the ground, and wherein a single groove extends along a length of the striking face; and

(b) a runner provided on the bottom side of the blade wherein during putting, the runner acts to space the bottom side of the blade from the ground.

8. (original) The putter of Claim 7 wherein the runner extends between the first linear edge and a second linear edge, and is convexly rounded between the linear edges.

9. (original) The putter of Claim 7 wherein a bottom of the head is convexly rounded between the ends of the blade.

10. (canceled)

11. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein the bottom of the head is provided with a convexly rounded semicircular protrusion extended from the blade as the runner.

5 12. (canceled)

13. (currently amended) The putter of ~~any one of Claims 7, 8 or 9 wherein the blade is metal or metal substitute and~~ having a non-metal portion on the top and bottom sides of the blade.

10 14. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein the shaft of the putter is mounted to the top side of the blade adjacent to the first linear edge where the edge strikes the ball.

15. (canceled)

15

16. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein the striking face is less than about 0.25 inch (6.4 mm) thick between the sides defining the first linear edge.

17. (canceled)

20

18. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein the striking face is sharp, pointed, flat, or curved.

19. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein a single groove extends along a length of the striking face.

5 20. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein the striking face is curved with a radius of curvature less than a radius of the golf ball.

21. (currently amended) The putter of ~~any one of Claims 7, 8 or 9~~ wherein the striking face is capable of striking the golf ball at, above, or below a median of the golf ball.

10

22. (original) A modular putter head for attachment to a head of an existing putter which comprises:

(a) an elongate flat blade with a first linear edge extending between ends of the blade and top and bottom sides of the blade, and forming a striking face for a golf ball, which during
15 putting strikes the ball in an essentially linear, horizontal line of contact, and with a second linear edge parallel to the first linear edge and extending between the ends of the blade; and

(b) attachment means for securing the blade to the head of the putter.

23. (original) The putter head of Claim 22 wherein the bottom side of the blade provides a
20 runner which is adjacent to a ground and the top side is attached to a shaft.

24. (original) The putter head of Claim 22 wherein the runner is narrow and convexly curved, so that in use the runner minimizes skidding against the ground.

25. (canceled)

5

26. (canceled)

27. (original) A golf putter for fitting to an individual golf stroke comprising:

(a) a shaft with a proximal end and a distal end;

10 (b) attachment means for pivotably attaching a putter head to the distal end of the shaft;

(c) an elongate flat blade having opposed ends and a top side and a bottom side, and pivotably attached on the top side to the attachment means allowing for selection of a desired angle of the blade relative to the shaft;

15 (d) one or more weights removably connected to the elongate flat blade; and

(e) an adjustable runner having a height and attached to the bottom side of the elongate flat blade.

28. (canceled)

20

29. (original) A method of fitting a golf putter to an individual golf stroke of a person which comprises the steps of:

(a) providing a golf putter to a person comprising a shaft with a proximal end and a distal end, an attachment means for pivotably attaching a putter head to the distal end of the shaft, an elongate flat blade having opposed ends and a top side and a bottom side and pivotably attached on the top side to the attachment means allowing for selection of a desired angle of the blade relative to the shaft, one or more weights removably connected to the elongate flat blade, and an adjustable runner having a height and attached to the bottom side of the elongate flat blade;

(b) determining the golf stroke of the person;

(c) adjusting a runner height to the golf stroke of the person;

(d) weighting the putter with the one or more weights to set a center of mass of the head to a point behind a contact area of the blade with a golf ball, particular to the golf stroke of the person;

(e) pivoting the shaft with respect to the elongate flat blade at a pivot angle to allow the blade to remain parallel to the ground for the particular golf stroke of the person; and

(f) measuring the runner height, the one or more weights and the desired angle for the purpose of fitting the putter to the particular golf stroke of the person.